

ToLEDo AVANT T8 CCG and AC

ToLEDo AVANT T8 CCG L1061 2000LM 840 50K RL
0030260



Product features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps
- Omni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes
- High lumen package - 2000lm
- High lumen efficacy - 150 lm/W
- Switching cycles - 200,000X
- Average life 50,000 hours lifespan
- Lamp length - 1061mm
- Wide beam angle
- High power factor
- Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applications
- Suitable for operation with electromagnetic gears / CCG and direct mains operation (220-240V)
- 5-Year warranty



NOTES

undefined

PRODUCT OVERVIEW

Product name	ToLEDo AVANT T8 CCG L1061 2000LM 840 50K RL
Technology	LED
Lamp shape	Tube, single-ended
Type	LED exchangeable
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open
General application	Hospitality, Logistics & Industry, Residential & Consumer
ETIM Class	EC001959
Warranty	5 years
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Wattage (W)	13.3
Dimmable	No
IP rating	IP20
Product EAN number	5410288302607

DATA TABLE

General data

ToLEDo AVANT T8 CCG and AC

ToLEDo AVANT T8 CCG L1061 2000LM 840 50K RL

0030260

Product name	ToLEDo AVANT T8 CCG L1061 2000LM 840 50K RL
Technology	LED
Lamp shape	Tube, single-ended
Type	LED exchangeable
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open
General application	Hospitality, Logistics & Industry, Residential & Consumer
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
Warranty	5 years

Optical data

Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0

Electrical data

Wattage (W)	13.3
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Control gear required	No
Dimmable	No
Inrush Current (A)	16.6
Lamp Energy Label (class)	D

Lifetime data

Lifespan L70 B50	50000
------------------	-------

Physical data

IP rating	IP20
Nominal Product Length (mm)	1060
Nominal Product Diameter (mm)	28
Weight (kg)	0.16

Packaging

Single packaging type	Carton
Product EAN number	5410288302607
Packaging single length / height (cm)	109.8
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (outer)	15410288302604
Units per outer package	10

ToLEDo AVANT T8 CCG and AC


ToLEDo AVANT T8 CCG L1061 2000LM 840 50K RL
0030260

Packaging outer length / height (cm)	115.6
Packaging outer width (cm)	22.6
Packaging outer depth (cm)	11.3


Safety data

Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture

PHOTOMETRY



TECHNICAL DRAWINGS




ToLEDo AVANT T8 CCG and AC

ToLEDo AVANT T8 CCG L1061 2000LM 840 50K RL
0030260



SYLVANIA

0030260



14
kWh/1000h




2019/2015

ToLEDo AVANT T8 CCG and AC
ToLEDo AVANT T8 CCG L1061 2000LM 840 50K RL
0030260



0030260



14
kWh/1000h



2019/2015