

Start Batten DALI

Start Batten 1800 9000lm DALI 830/840

0048985



Product features

- LED batten, T8 replacement, ease of installation through 2 part push-in design of the housing, Traffic white (RAL9016) iron housing, 8700 / 8900lm, 65W, 134/137lm/W, Integrated switch allows to choose between warm white (3000K) and neutral white (4000K) colour temperatures, CRI80, 3 step MacAdam ellipse, symmetric wide beam angle, Class I, 120000 hrs L70B50 lifespan, DALI driver, IK08, IP20, 1800 x 64 x 65mm (LxWxH) dimensions, 1.83kg weight. BESA compatibility. End cap incorporates 20mm conduit knock out.



PRODUCT OVERVIEW

Product name	Start Batten 1800 9000lm DALI 830/840
Technology	LED
Cap/Base	N/A
Housing	Steel
General application	Logistics & Industry
ETIM Class	EC000109
E-number FI	4279491
Warranty	5 years
Fixture luminous flux (lm)	8900
Luminaire efficacy (lm/W)	137
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	145x110
Photobiological Risk Group	RG1
Total power consumption (W)	65
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK08
Product EAN number	5410288489858

DATA TABLE

General data

Product name	Start Batten 1800 9000lm DALI 830/840
Technology	LED
Cap/Base	N/A
Housing	Steel

Start Batten DALI

Start Batten 1800 9000lm DALI 830/840

0048985

General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000109
E-number FI	4279491
Warranty	5 years

Optical data

Fixture luminous flux (lm)	8900
Luminaire efficacy (lm/W)	137
Correlated colour temperature range (K)	3000 - 4000
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	145x110
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	65
Primary Supply/Product voltage - min (V)	240.0
Primary Supply/Product voltage - max (V)	220
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	20
Electrical protection	Class I
Control gear required	Yes
Control gear type	LED driver constant current
No. Of switching cycles before premature failures	>50000
Dimmable	Yes
Dimming method	DALI-2
Drive current (mA)	400
Inrush Current (A)	38.2
Inrush Duration (µs)	289
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	5
Max. products per 13A C Breaker	7
Max. products per 16A C Breaker	9
Max. products per 20A C Breaker	11
Max. products per 10A B Breaker	4
Max. products per 13A B Breaker	4
Max. products per 16A B Breaker	5
Max. products per 20A B Breaker	7
Connectable conductor cross section - Max (mm²)	1.5

Start Batten DALI

Start Batten 1800 9000lm DALI 830/840

0048985

Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B50	120000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK08
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1800
Nominal Product Width (mm)	64
Nominal Product Height (mm)	65
Weight (kg)	1.831



Packaging

Product EAN number	5410288489858
Packaging single length / height (cm)	180.0
Packaging single width (cm)	6.4
Packaging single depth (cm)	6.5
DUN14 (outer)	15410288489855
Units per outer package	6
Packaging outer length / height (cm)	182.0
Packaging outer width (cm)	15.3
Packaging outer depth (cm)	22.7

Safety data



Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY



Start Batten DALI

Start Batten 1800 9000lm DALI 830/840
0048985



TECHNICAL DRAWINGS

