

## Resisto fixed output

Resisto 1500 IP66 4000lm 840

0010243



### Product features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 4000lm; 30W; 133lm/W; 4000K; SDCM<5; non dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark.



## PRODUCT OVERVIEW

Product name	Resisto 1500 IP66 4000lm 840
Technology	LED
Housing	PC Polycarbonate
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4357056
Warranty	5 years
Fixture luminous flux (lm)	4000
Luminaire efficacy (lm/W)	133
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Colour Consistency (SDCM)	5
Glare control	< 23
Photobiological Risk Group	RG1
Electrical protection	Class I
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288102436

## DATA TABLE

### General data

Product name	Resisto 1500 IP66 4000lm 840
Technology	LED
Housing	PC Polycarbonate
General application	Logistics & Industry
Operating temperature range (°C)	-20°C - 40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892

## Resisto fixed output

Resisto 1500 IP66 4000lm 840  
0010243

E-number FI	4357056
Warranty	5 years

### Optical data

Fixture luminous flux (lm)	4000
Luminaire efficacy (lm/W)	133
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Colour Consistency (SDCM)	5
Beam angle (Rated) (°)	110
Distribution type	Diffuse
Glare control	< 23
Photobiological Risk Group	RG1

### Electrical data

Mains voltage (V)	220-240V~
Lamp power factor	0.95
Electrical protection	Class I
No. Of switching cycles before premature failures	>50000
Dimmable	No
Drive current (mA)	350
Inrush Current (A)	5.5
Inrush Duration (µs)	20
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	41
Max. Luminaires per 13A C Breaker	53
Max. Luminaires per 16A C Breaker	65
Max. Luminaires per 20A C Breaker	82
Max. Luminaires per 10A B Breaker	41
Max. Luminaires per 13A B Breaker	53
Max. Luminaires per 16A B Breaker	65
Max. Luminaires per 20A B Breaker	82

### Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	69000
Lifespan L90 B10	31000

### Physical data

Housing colour	Grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1500

## Resisto fixed output

Resisto 1500 IP66 4000lm 840  
0010243

Nominal Product Width (mm)	87
Nominal Product Height (mm)	80
Weight (kg)	1.87

### Packaging

Single packaging type	Carton
Product EAN number	5410288102436
Packaging single length / height (cm)	150.5
Packaging single width (cm)	10.0
Packaging single depth (cm)	8.5
DUN14 (outer)	05410288102436
Units per outer package	1
Packaging outer length / height (cm)	150.5
Packaging outer width (cm)	10.0
Packaging outer depth (cm)	8.5

### Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------


## PHOTOMETRY

Distance [m]	Cone diameter [m]	E(0°)	E(C90)	E(C0)
0.5	1.43 1.32	9145	496	989
1.0	2.86 2.63	1286	122	142
1.5	4.28 3.95	572	84	63
2.0	5.71 5.27	322	30	36
2.5	7.14 6.59	206	19	23
3.0	8.57 7.99	143	14	16

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 105.0°)

— C90 - C270 (Half beam angle: 110.0°)



## TECHNICAL DRAWINGS

