

Start Waterproof Housing


START WATERPROOF 1200 HOUSING 1X

0047922



Product features

- Luminaire, polycarbonate housing • Single version, 1200mm • Protection type IP65 • Luminous flux and light colour vary depending on LED tubes used • To be used with T8 LED tubes • Easy to install with stainless steel fixing brackets included for ceiling mounting • Ideal for any industrial facilities, garages, car parks, workshops.



PRODUCT OVERVIEW

Product name	START WATERPROOF 1200 HOUSING 1X
Technology	LED
Cap/Base	G13
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4309056
Warranty	3 years
LOR (%)	75
Electrical protection	Class I
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288479224

DATA TABLE

General data

Product name	START WATERPROOF 1200 HOUSING 1X
Technology	LED
Cap/Base	G13
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4309056
Warranty	3 years

Optical data

LOR (%)	75
Distribution type	Direct

Start Waterproof Housing

START WATERPROOF 1200 HOUSING 1X
0047922

Electrical data

Electrical protection	Class I
Glow Wire Test (°C)	650

Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1260
Nominal Product Width (mm)	69
Nominal Product Height (mm)	78
Weight (kg)	0.81

Packaging

Single packaging type	Carton
Product EAN number	5410288479224
Packaging single length / height (cm)	128.0
Packaging single width (cm)	6.9
Packaging single depth (cm)	5.2
DUN14 (outer)	15410288479221
Units per outer package	1
Packaging outer length / height (cm)	128.0
Packaging outer width (cm)	6.9
Packaging outer depth (cm)	5.2

TECHNICAL DRAWINGS

