

## Start Waterproof Housing

### START WATERPROOF 1500 HOUSING 1X

0047924



#### Product features

- Luminaire, polycarbonate housing • Single version, 1500mm • Protection type IP65 • Luminous flux and light colour vary depending on LED tubes used • To be used with T8 LED tubes • Easy to install with stainless steel fixing brackets included for ceiling mounting • Ideal for any industrial facilities, garages, car parks, workshops.



## PRODUCT OVERVIEW

Product name	START WATERPROOF 1500 HOUSING 1X
Technology	LED
Cap/Base	G13
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4309058
Warranty	3 years
LOR (%)	75
Electrical protection	Class I
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288479248

## DATA TABLE

### General data

Product name	START WATERPROOF 1500 HOUSING 1X
Technology	LED
Cap/Base	G13
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4309058
Warranty	3 years

### Optical data

LOR (%)	75
Distribution type	Direct

## Start Waterproof Housing

*START WATERPROOF 1500 HOUSING 1X*  
**0047924**

### Electrical data

Electrical protection	Class I
Glow Wire Test (°C)	650

### Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1560
Nominal Product Width (mm)	69
Nominal Product Height (mm)	78
Weight (kg)	1.11

### Packaging

Single packaging type	Carton
Product EAN number	5410288479248
Packaging single length / height (cm)	158.0
Packaging single width (cm)	6.9
Packaging single depth (cm)	5.2
DUN14 (outer)	15410288479245
Units per outer package	1
Packaging outer length / height (cm)	158.0
Packaging outer width (cm)	6.9
Packaging outer depth (cm)	5.2

## TECHNICAL DRAWINGS

